

## **Bel-Air Padded Underlayment**

3mm Padded Underlayment With Plastic Backing



Bel-Air Padded Underlayment was specially made to absorb sound, It helps reduce noise levels in the living space and under the floor. eliminates seeking and hollow sounds as well as provide structural stability of your floor preventing it from sagging and buckling.

### **ROLL DIMENSIONS:**

 Ft.2 Per Roll:
 201

 Thickness:
 3.0mm

 Density:
 380kgs/m3

 Width:
 45" (3.75Ft.)

 Length:
 640" (54 Ft.)

Weight: 22 lbs.
Rolls/Pallet: 50 Rolls
Pallet Dimensions:

Length: 48" Width: 42"

Height: 72"

### **FEATURES:**

100% Vapor Barrier 100% Electrical Insulator 100% Mold & Mildew Resistant 100% Environment friendly

### Sound & Impact Properties

Impact Insulation Class (IIC): 69dB | Field Impact Insulation Class (FIIC): 65dB Sound Transmission Class (STC): 70dB

#### **CLASSIFICATION STANDARD**

Water vapour trans. rate: ASTM E96 1.8g/m2.24hr Water absorption 28 days: JIS 6767 0.03mg/cm2 Compr. strength (25% Comp): ISO844 70kpa

Moisture protection SD Value: ≥75





# Bel-Air Padded Underlayment

3mm Padded Underlayment With Plastic Backing



Bel-Air Padded Underlayment was specially made to absorb sound, It helps reduce noise levels in the living space and under the floor. eliminates seeking and hollow sounds as well as provide structural stability of your floor preventing it from sagging and buckling.



Field Impact Insulation Class (FIIC): 65dB



Impact Insulation Class (IIC): **69dB** 



Sound Transmission Class (STC): **70dB** 



100% Environment friendly



100% Mold & Mildew Resistant



100% Electrical Insulator



100% Vapor Barrier