



Bel-Air White Foam

2.8MM White EPE Foam Combined With Aluminum Foil



Bel-Air White Foam Underlayment is manufactured by using a EPE (Expanded Polyethylene) foam, a close-cell polyethylene microcellular foam that is well known for its ability to maintain its dimensional structure when pressed combined with a layer of aluminum foil for moisture, thermal and sound resistance.

ROLL DIMENSIONS:

Ft.2 Per Roll: 200

Thickness: 2.8 mm.

Density: 25kg/m³

Width: 44" (3.75Ft.)

Length: 640" (53 Ft.)

Weight: 3.1 lbs.

Rolls/Pallet: 50 Rolls

Pallet Dimensions:

Length: 48" **Width:** 42"

Height: 72"

FEATURES:

100% Vapor Barrier

100% Electrical Insulator

100% Mold & Mildew Resistant

100% Environment friendly

Sound & Impact Properties

Impact Insulation Class (IIC): 62dB | Sound Transmission Class (STC): 63dB

CLASSIFICATION STANDARD

STC Classification: ASTM E90-04, 54dB

IIC Classification: ASTM E492-04, 51dB

Thermal Conductivity: 0.15 BTU/Hr.Sq.In

Fire Resistance: UL 94 HFI, F.A.R. 25.83

Water Absorption: 0.002 Lbs Per Cubic Feet



Bel-Air White Foam

2.8MM White EPE Foam Combined With Aluminum Foil



Bel-Air White Foam Underlayment is manufactured by using a EPE (Expanded Polyethylene) foam, a close-cell polyethylene microcellular foam that is well known for its ability to maintain its dimensional structure when pressed combined with a layer of aluminum foil for moisture, thermal and sound resistance.



Impact
Insulation
Class (IIC): **62dB**



Sound
Transmission Class
(STC): **63dB**



100%
Environment
friendly



100% Mold
& Mildew
Resistant



100%
Electrical
Insulator



100%
Vapor
Barrier