

All warranties listed under this warranty guide are given to the original retail purchaser / end-user of our first-quality products and are non-transferrable. Under the manufacturer's Water resistant Laminate Flooring Limited Warranty, we warrant to the original retail purchaser of the products that from the date of the original purchase for the applicable period set forth in the chart below, that:

1. In normal household conditions or a light commercial indoor setting, when installed and maintained according to our recommended maintenance guide, the design layer of the floor will not wear through, fade from normal sunlight or artificial lighting, or stain. Gloss reduction does not constitute "wear."

2. The floor will be water resistant from normal everyday household spills & resist topical water damage. At no time should standing liquids/water be left on the floor - planks will not swell, delaminate, or peak at seams due to topical spills where the liquid is wiped up accordingly and the floor is allowed to dry completely.

2.a. The floor will be water resistant for up to 72hours when said liquid is poured from the upper side

3. The floor will be free of manufacturing defects when purchased in its original manufactured condition.

4. In normal household conditions or a light commercial indoor setting, the floor joints will remain secure.

Limited Residential Warranty Period Limited Commercial Warranty Period

Water resistant Laminate Flooring
All Residential and Light
Commercial Use
25 Years 10 Years

All Water resistant laminate warranties under this guide are subject to the following conditions:

1. The warranty applies to North America. The flooring must be installed in accordance with the installation guidelines provided. The flooring must also be cleaned, maintained, and cared for in accordance with the instructions provided.

2. The manufacturer warrants its products against manufacturing defects that exist in its products prior to product installation. Flooring installed with known defects is not covered under this warranty. All planks must be inspected for possible, recognizable defects before and during the installation as any right to claim under warranty becomes invalid after planks with visible defects have been installed. Warranty claims can only be accepted if the planks were delivered by the dealer in its original packaging.

3. The surface wear or damage must not be the result of abusive conditions, misuse of the product, freight damage, modification, alteration, repairs or service of the product by anyone other than the authorized manufacturer representative, improper care or maintenance (refer to provided care and maintenance guidelines), or accidents, such as but not limited to severe impact, scratching, cutting, negligence or chemical damage. Note that gloss reduction is not considered surface wear. The surface wear must be readily visible from the distance of 6 feet, measuring at least 1 square inch. Wear-through at the edges of the product is excluded from the warranty.

4. According to proper installation guidelines, flooring must be installed in a dry, climate controlled, indoor, residential /light commercial environment. A moisture test must be performed to determine if excessive moisture exists in the subfloor. When using a calcium chloride moisture test for concrete subfloors (ASTM F1869), values must be ≤ 5 lbs/1000ft² / 24-hr or <80% RH with an in-situ probe (ASTM F2170). A polyethylene film vapor barrier is not required over wood subfloors. Moisture readings of wood subfloors must be $\leq 12\%$ throughout the entire installation.

5. The manufacturer is not liable for the performance of the subfloor. This warranty excludes damage in the subfloor or underneath the flooring due to water, moisture, mildew, and including but not limited to hydrostatic pressure.

6. Approved accessories must be used to validate warranty. Please contact your nearest dealer or the manufacturer directly for more details.